


ARAMIS®

“FENCING FOR ALL” ARAMIS KIT: ASSEMBLING INSTRUCTIONS -CAUTIONS



1-Insert the guard from the tip of foil and closing-in the upper part of the blade



2- Insert the rubber tip-cover-button by hand or using proper tool



3-In order to insert or replace the 12 v battery extract the holding battery/buzzer using a small screwdriver



4- Assemble the 2 brackets with the knobs on issue

The padded posterior bracket can be adjusted as function of user needs.
Attention do not bend : it is not a spring !

CAUTIONS

- Aramis plastic foil and mask can be used by people with over 6 years age.
- When fencing with Aramis plastic foil you must dress the mask, a tracksuit, a glove and a parabraest (for the women).
- The Aramis plastic mask must be used with the Aramis plastic foil. The Company producer of Aramis product do not take the responsibility for damages caused to the people when the Aramis mask is used with a fencing tool different than the Aramis plastic foil and when Aramis foil is used without the Aramis plastic mask.
- During fencing exercises do not take out the mask.
- We suggest not to make Fencing with plastic foil on metallic piste, since in this case the reliability of rubber tip cover-button could be very poor.
- Do not address the plastic foil against who does not dress the mask.
- During exercises break or transfers the tip cover-button of the foil must be addressed versus down.
- During fencing never address the shoulders against the partner.
- The plastic foil has not to be bent and has not be placed at very high or very low temperatures.
- The plastic foil tip has not be knocked against the floor.
- The hits have not to be given with violence.
- Fighting man to man and fencing actions very closer are forbidden .

NASYCON

MADE BY

SAS Strada del Lauro 26 10132 Turin- Italy, sales@nasycon.com

Read and Keep the above instructions that the Company producer enclose to every single article sold in according to CE approval ref Certificate of Conformity issued on date 27-11-2001 file C2697ext2006